



Chemical Specialties Manufacturing Corporation

901 N. Newkirk Street / Baltimore, MD 21205 / (800) 638-7370

MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Degree of hazard: 4 = Extreme, 3 = High, 2 = Moderate, 1 = Slight, 0 = Insignificant

Health 1
Flammability 2
Reactivity 0

SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME: Wet Solvent

DATE REVIEWED: October 2, 2003

DOC CODE: Wet Solvent

CHEMICAL FAMILY: Mixture.

EMERGENCY 24-HOUR TELEPHONE # 1-800-424-9300 (CHEMTREC)

N/A = Not applicable or Not available.

N/D = Not determined.

SECTION II: COMPOSITION/ INFORMATION ON INGREDIENTS

This product has not been tested as a whole for health effects on animals or humans. According to the OSHA Hazardous Communications Standard (29 CFR 1910.1200) any hazardous ingredients that comprise >1.0% of the material and any carcinogenic ingredients that comprise >0.1% must be listed on the MSDS. When individually tested at 100% ingredients in the make-up of this product posed the following health hazards.

SECTION II a: HAZARDOUS INGREDIENTS >1.0%

Chemical Name	CAS #	PEL	TLV
2-Butoxyethanol	111-76-2	25 ppm	25 ppm

SECTION II b: CARCINOGENIC INGREDIENTS AT >0.1%

None.

SECTION III: HAZARDS IDENTIFICATION

EYES: May cause severe eye irritation and possible burns.
SKIN: May cause severe skin irritation and possible burns.
INHALATION: Breathing dust may cause irritation of the upper respiratory tract.
INGESTION: May cause abdominal discomfort, nausea and diarrhea.

SECTION IV: FIRST AID PROCEDURES

EYES: Flush with water for at least 15 minutes. If irritation persists consult physician.
INGESTION: Drink 1 to 2 glasses of water. Consult physician.
INHALED: Remove to fresh air. If symptoms persist or are severe seek prompt medical assistance.
SKIN: Remove contaminated clothing. Thoroughly wash exposed area with soap and water.
PHYSICIAN: Treatment based on judgment of attending physician.

Wet Solvent

SECTION V: FIRE AND EXPLOSION DATA

FLASH POINT: 175 deg F, 79.4 deg C.
AUTO-IGNITION TEMPERATURE: N/D
EXPLOSIVE LIMITS - UEL: N/D LEL: N/D
EXTINGUISHING MEDIA: Alcohol foam, water fog, CO₂ or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH/MSHA approved self-contained positive pressure breathing apparatus and protective clothing where this material is involved in a fire.
UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Scoop up spilled material and re-use if possible. If material cannot be used dispose in landfill.

SECTION VII: HANDLING AND STORAGE

No special precautions required.

SECTION VIII: PROTECTION MEASURES

VENTILATION: Local exhaust or dilution ventilation is necessary in poorly ventilated areas.
GLOVES: Rubber gloves.
RESPIRATORY: When mists or aerosols are anticipated, wear NIOSH/MSHA approved respirator equipped with organic vapor cartridges with high-efficiency particulate filters.
EYE: Safety glasses. Wear splash goggles when mists or aerosols are anticipated.
OTHER PROTECTIVE EQUIPMENT: Body-covering clothing should be worn.

SECTION IX: PHYSICAL/CHEMICAL DATA

APPEARANCE AND ODOR: Clear colorless liquid with mild ethereal odor.	WATER SOLUBILITY, % BY WT: 100
SPECIFIC GRAVITY: 0.9 % VOLATILE BY WT.: 100	FREEZING POINT: -95 F
WT/GAL: 7.5 lbs. BOILING POINT: 340 F	VAPOR PRESSURE: 0.6 mm Hg
EVAPORATION RATE (BUTYL ACETATE = 1): 0.08	VAPOR DENSITY (AIR = 1): 4.1

SECTION X: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
INCOMPATIBILITY: Strong Acids
HAZARDOUS DECOMPOSITION/COMBUSTION PRODUCTS: Possibly oxides of carbon or nitrogen, ammonia, halide compound and other unidentified organic compounds.

SECTION XI: TOXICOLOGICAL INFORMATION OF INGREDIENTS

2-Butoxyethanol: Oral rat LD50 is 470 mg/kg; dermal rabbit LD50 is 220 mg/kg; rat LC50 is 700 ppm in 7 hrs. OSHA PEL and ACGIH TLV are 25 ppm, skin.

SECTION XII: ECOLOGICAL INFORMATION

Ready to use solution is biodegradable. No other information is available.

SECTION XIII: SPILL, LEAK AND DISPOSAL PROCEDURES

WASTE DISPOSAL: In accordance with Federal, state and local regulations.
NEUTRALIZING CHEMICALS: Water.

Wet Solvent

SECTION XIV: TRANSPORT INFORMATION PER 49 CFR 172.101

GROUND TRANSPORTATION:

Combustible Liquid (2-Butoxyethanol), n.o.s., NA 1993, PG III. Packaging exemptions may apply.

AIR TRANSPORTATION:

Please refer to FAA regulations.

MARITIME TRANSPORTATION:

Flammable Liquids, (2-Butoxyethanol), n.o.s., Class 3, UN 1993, PG III.
IMDG PAGE #: 3126.

SECTION XV: REGULATORY INFORMATION**Domestic:**

TSCA: All ingredients are listed on the TSCA chemical substance inventory.

SARA Section 313 Ingredients: 2-Butoxyethanol.

California Prop 65 Ingredients: None.

International:

European labeling requirements:

Symbol: Harmful

R-Sentences: Xn; R20/R21/R22-R37

S-Sentences: S2, S24, S25, S46

Canadian:

WHMIS Hazard Class: D2B.

SECTION XVI: OTHER INFORMATION

One should always use chemicals with awareness of potential hazards, known and unknown, and their effect on the human system. We urge users to minimize employee exposure to all chemicals, including this product and to keep the level of exposure commensurate with good industrial hygiene practices.

DISCLAIMER OF LIABILITY

The manufacturer and seller warrants that this product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.