

DESCRIPTION

FinishJob35 represents a true advance in floor finish performance. This super high solids formula produces unmatched "off-the-mop" gloss with extended gloss retention. Utilizing exclusive Advanced Polymer Technology, this superior floor coating will produce maximum gloss with fewer coats than conventional floor finishes. Combination sealer / finish saves product costs. Exceptional response to UHS burnishing.

PRODUCT FEATURES / BENEFITS

- Applicable for use in high traffic areas / Achieves maximum versatility
- MPS77 Advanced Polymer Technology produces exceptional gloss from fewer coats
- Sealer/finish combination for product cost savings
- Maximum resistance to scratches and scuffs

DIRECTIONS FOR USE

Floor Preparation: Using Janilink Bulldozer II, No-rinse, No-scrub Liquifying Stripper, strip off old finish and wax following product label directions. For baseboards and corners, use Janilink Strip it Baseboard Stripper. Make sure the floor is clean and dry before applying finish.

Application: Using a clean mop or applicator apply a thin uniform coat of FinishJob35. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period.

High Speed Buffing and Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of

1500- 3000 rpm (electric, battery or propane). Dust mop using Janilink Dustmop treatment prior to high speed buffing or burnishing. Buff or dry burnish using an aggressive natural hair burnishing pad. For spray buffing, mop-on restoration or auto scrubbing use Janilink Spray Mister2000 Ultra High Speed Kleen & Burnish. **Maintenance:** Dust mopping daily using mop treated with Janilink Dustmop Treatment. Use a recommended Janilink neutral floor cleaner for routine cleaning. Spray buffing to remove embedded soils is recommended using Janilink Spray Mister2000. Worn areas, or the entire floor, may be scrubbed and recoated as required to maintain a uniform high gloss.

SPECIFICATIONS

Type	Pure acrylic polymers	Odor	Typical acrylic
Total Solids (%).....	34.5 ± 0.5	Film Appearance	Clear
pH	8.5 ± 0.5	Powdering	None
Coverage (sq. ft./gal).....	up to 3,000	Flash Point	None
Drying Time (minutes)	30	Slip Resistant	Yes
Color	White, opaque liquid	Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION


CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with skin and eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage.

FIRST AID: For Eyes: Flush thoroughly with water for at least fifteen minutes. If irritation persists seek medical attention. For Skin: Wash thoroughly with soap and water. If irritation persists


seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

KEEP FROM FREEZING

FOR PROFESSIONAL USE ONLY



FLOOR CARE



HMIS HAZARD CODE	
1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
B	PERSONAL PROTECTION